

# POWER ACOUSTIK

## SPECTRUM analyzer



### WHATS IN THE BOX



Spectrum Analyzer



Mounting Bracket



Double-Sided Adhesive



Power Cable



Mounting Screws



USB Cable

### INSTALLING THE SPECTRUM ANALYZER

PowerAcoustik Spectrum Analyzer can be mounted on flat surfaces in your car two ways:

#### Double Sided Adhesive

1. Clean the surface area around the desired location using a damp microfiber towel and mild detergent if necessary.
2. Remove the protective paper from one side of the included double sided adhesive.
3. Apply the exposed adhesive side to the back of the Spectrum Analyzer.
4. Remove the protective paper from the opposite side of the double sided adhesive.
5. Install the Spectrum Analyzer by firmly pressing the Spectrum Analyzer onto the desired mounting surface.

#### Angled Stand / Support Bracket

1. Secure the angled support bracket to a flat surface using two provided coarse thread screws or apply the double sided adhesive to the bottom of the bracket.
2. If using the double sided adhesive, remove the protective paper from the opposite side of the double sided adhesive & install the bracket by firmly pressing it onto the desired mounting surface.
3. Secure the Spectrum Analyzer to the angled support bracket using the provided fine thread screws into the back of the Spectrum Analyzer.



### POWERING THE SPECTRUM ANALYZER

PowerAcoustik Spectrum Analyzer can be powered two ways:

#### USB Cable

1. Insert the oval Type-C end of the USB cable into the Type-C input on the left side of the Spectrum Analyzer.
2. Connect the square Type-A end of the USB cable into an available USB Charging device.

#### Direct Power

1. Insert the white end of the power cable into the power port on the back of the Spectrum Analyzer.
2. Connect the red wire to positive power & the black wire to ground of the vehicle's electrical system.

